

O₂
H₂S
CO
CH₄
SO₂
NH₃
CO₂
O₃
Cl₂
NO₂

Gas-Pro

Confined Space Entry Monitor

Portable 5 gas detector



Gas-Pro

Designed with confined space workers and fleet managers in mind, Gas-Pro offers detection of up to 5 gases in a compact, rugged solution capable of withstanding harsh environments and everyday use.

Confined Space Solution

- Easy to see top mount display
- Internal pump (option)
- Automatic fail safe flow plate recognition
- Specific and unique Pre-Entry mode
- +ve Safety™ (Positive Safety) tri-colour status indicator
- Integral over moulded anti-shock case
- Simple single button operation
- Portable, wall and desk mount gas test solutions

Flexible

- Tailor +ve Safety™ to organisational requirements
- Monitor 5 gases from many different options
- Multipurpose; pumped and diffusion solutions offering multiple uses within one compact detector



BE SAFE
POSITIVE
+ve Safety™

CROWCON
Gas Detection You Can Trust

Gas-Pro

Compact and rugged confined space entry monitor capable of detecting up to 5 gases.

Gases & Ranges

Gas-Pro offers a wide range of sensors, a number of which are shown below. Gases and ranges may vary by country and application. Each gas channel has two instantaneous alarms with toxic channels also having TWA alarms.

Gas	Range	Typical Alarms	Resolution
Dual toxic	H ₂ S 0-100 ppm CO 0-500 ppm	5 ppm 30 ppm	1 ppm 1 ppm
Oxygen	0-25% VOL	19%/23% VOL	0.1% VOL
Flammable*	0-100% LEL	20% LEL	1% LEL
Carbon dioxide	0-5% VOL	0.5% VOL	0.01% VOL
Scheduled for release (contact Crowcon for timescales)			
Ammonia	0-100 ppm	25 ppm	1 ppm
Sulphur dioxide	0-20 ppm	1 ppm	0.1 ppm
Ozone	0-1 ppm	0.1 ppm	0.01 ppm
Chlorine	0-5 ppm	0.5 ppm	0.1 ppm
Chlorine dioxide	0-1 ppm	0.1 ppm	0.1 ppm
Nitric Oxide	0-100 ppm	25 ppm	1 ppm
Nitrogen dioxide	0-20 ppm	1 ppm	0.5 ppm

* Pellistor calibration available for methane. Other calibrations (butane, pentane, propane and ethylene) scheduled for release, contact Crowcon for details.

Gas Test Solutions

Solutions for in-field and on-site gas test, calibration and data capture

- Q-Test:** Quick and simple in-field testing
- I-Test:** Intelligent wall or desk mount station
- S-Test:** Service and maintenance of up to 5 detectors

Specification:

Size (d x h x w)	43 x 130 x 84mm (1.7 x 5.1 x 3.3 inches)
Weight	309g 4 gas (10.8oz)/340g pumped (11.9oz) 333g 5 gas (11.7oz)/362g pumped (12.7oz)
Alarms	Audible >95dB @ 30cm (98dB @30cm in loud mode) Visual - all angle dual red/blue LEDs Vibrating alert
Display	Top mount for ease of view With dual colour backlight (green/red)
Data Logging	125hrs @ 10 second intervals (45,000 logs)
Event Logging	Alarm, over range, calibration, bump, on/off, TWA, 1000 events
Battery	Rechargeable Li-ion, >14 hrs (13 hrs pumped operation) based on CH ₄ , O ₂ , H ₂ S, CO Typical charge time 7.5 hrs
Sampling	Internal pump as option
Operating temperature	-20°C to +55°C (-4°F to +131°F) ⁺
Storage	-25°C to +65°C (-13°F to +149°F)
Humidity	10 to 95% RH ⁺
Ingress Protection	Independently tested to IP65 & IP67
Approvals	IECEX: Ex d ia IIC T4 Gb Tamb -20°C to +55°C ATEX: Ex d ia IIC T4 Gb Tamb -20°C to +55°C UL: Gas detector use in hazardous locations Class 1 Division 1 Groups A,B,C, and D only as to intrinsic safety
Compliance	FCC and CE Complies with EMC Directive 2004/108/EC EN50270 and ICES-003
Interface	Data connection for gas test solutions and direct to PC
Charging	Direct connect to multiregion power supply Vehicle charger adaptor Desk top cradle USB power and communications lead

⁺Dependant on sensor configuration

A HALMA COMPANY



UK: 2 Blacklands Way, Abingdon Business Park, Abingdon, OXON, OX14 1DY
+44 (0) 1235 557700 sales@crowcon.com

US: 21 Kenton Lands Road, Erlanger, Kentucky 41018-1845
+1 859 957 1039 salesusa@crowcon.com

NL: Vlambloem 129, 3068JG, Rotterdam
+31 10 421 1232 eu@crowcon.com

SG: Block 194 Pandan Loop, #06-20 Pantech Industrial Complex, Singapore, 128383
+65 6745 2936 sales@crowcon.com.sg

CN: Unit 316, Area 1, Tower B, Chuangxin Building, 12 Hongda North Road, Beijing Economic & Technological Development Area, Beijing, PRC 100176
+86 10 6787 0335 saleschina@crowcon.com

www.crowcon.com

Crowcon reserves the right to change the design or specification of the product without notice.
P08013/ENG Issue 1 Sept 2011

Area reserved for distributor stamp

CROWCON
Gas Detection You Can Trust